

# Application Configuration Settings

This chapter describes only the parameters that are typically edited during installation.

Before starting the application, make sure that no application is communicating on port 80.

After starting the application, the Configuration Manager is displayed, which needs to be filled in.

## Infoport Database Connection

DBMS	Server	Port	Database
<input type="text" value="MySQL"/>	<input type="text" value="127.0.0.1"/>	<input type="text" value="3306"/>	<input type="text" value="ip_beta"/>
User	Password		
<input type="text" value="root"/>	<input type="text" value="Dataprojekt"/>		
Timeout			
<input type="text" value="60"/>			
<input type="button" value="CHECK"/>			

## Active Directory OpenID

### LDAP Section

<input type="checkbox"/> Active	<input type="checkbox"/> Automatic Login	<input type="checkbox"/> Database Preference	<input type="checkbox"/> False Login As Host
<input type="button" value="CHECK"/>			

## Environment

☒ Persist Publication Image In Database

Relative Publication Path	Relative Cache Path	Relative Temp Path
<input type="text" value="publication"/>	<input type="text" value="cache"/>	<input type="text" value="temp"/>
<input type="button" value="CHECK"/>		

Revision #2

Created 7 April 2022 13:32:36

Updated 10 May 2022 18:03:03