

# Examples of Connection Strings

## Oracle:

"InfoportConnection\_Oracle" fill in:

- **"DATA SOURCE=(DESCRIPTION=(ADDRESS\_LIST=(ADDRESS=(PROTOCOL=TCP)(HOST=localhost)(PORT=1536)))(CONNECT\_DATA=(SERVER=DEDICATED)(SERVICE\_NAME=dedicated)));User Id=ip;Password=test;"**

## MS SQL:

"InfoportConnection\_SqlServer" fill in and change a password:

- **"Server=127.0.0.1;Database=eainfoport;User id=\*\*\*\*;Password=\*\*\*;"**

## MS SQL trusted connection:

If the database has integrated security for the domain, use the connection string below:

- **"Server=XXXXX;Database=YYYYY;Trusted\_Connection=True"**

## MySQL:

InfoportConnection\_MySql, fill in:

- **"Server=127.0.0.1;port=3306;Database=test\_eainfoportt3;Uid=EaInfoportT3;Pwd=info;"**

## MariaDB:

"InfoportConnection\_MySql":

- **"Server=127.0.0.1;port=3306;Database=test\_eainfoportt3;Uid=EaInfoportT3;Pwd=info;"**

[Other examples](#)

---

Revision #3  
Created 7 April 2022 13:43:46  
Updated 22 January 2024 08:29:03 by Karolína Kavanová