Examples of Connection Strings

Oracle:

"InfoportConnection_Oracle" fill in:

- **"DATA SOURCE=(DESCRIPTION=(ADDRESS_LIST=(ADDRESS=(PROTOCOL=TCP)(HOST=localhost)(PORT=1536)))(CONNECT_DATA=(SERVER=DEDICATED)(SERVICE_NAME=dedicated)));User Id=ip;Password=test;",**

MS SQL:

"InfoportConnection_SqlServer" fill in and change a password:

- **"Server=127.0.0.1;Database=eainfoport;User id=****;Password=***;",**

MS SQL trusted connection:

If the database has integrated security for the domain, use the connection string below:

- **"Server=XXXXX;Database=YYYYY;Trusted_Connection=True"**

MySQL:

InfoportConnection_MySql, fill in:

- **"Server=127.0.0.1;port=3306;Database=test_eainfoportt3;Uid=EaInfoportT3;Pwd=info;"**

MariaDB:

"InfoportConnection_MySql":

- **"Server=127.0.0.1;port=3306;Database=test_eainfoportt3;Uid=EaInfoportT3;Pwd=info;"**

Other examples

Revision #3
Created 7 April 2022 13:43:46
Updated 22 January 2024 08:29:03 by Karolína Kavanová