

# Infoport Database Connection

The first section in the configuration contains the Infoport database settings. (Database schema in which the program has all settings stored).

Infoport Database Connection [Connection Section](#)

DBMS Type	Server	Port	Database
MySQL	127.0.0.1	3306	infoporttest
User	Password		
root	*****		
Timeout			
60			

In the first item, we choose the type of database. There is a choice of three types.

1. MySQL with default port 3306
2. Microsoft SQL Server with default port 1433
3. Oracle with default port 152
4. PostgreSQL with default port 5432

After selecting the type, the value of the Port item will be filled in automatically.

DBMS

MySQL

Choose...

MySQL

Microsoft SQL Server

Oracle

PostgreSQL

The second item is setting the IP address of the database server. (If Infoport runs on the same machine with the database, just fill in the local IP address).

## Server

The third item is the database server port setting. By default, the pre-filled data according to the database type can be changed.

## Port

The fourth item is only relevant for MySQL and Microsoft SQL Server.

Fill in the name of the schema in which Infoport will create its tables. (If the schema is not created on the database server, Infoport will create it itself, provided the user has sufficient permissions in the database).

## Database

The other two items are user and password. You need to fill a user who has DML and DDL rights into our chosen database.

## User

## Password

The Timeout item is used to set the maximum length of a query within the database. It has an effect mainly on queries during the search.

## Timeout

---

Revision #4

Created 7 April 2022 11:12:24

Updated 2 November 2023 08:36:42 by Karolína Kavanová