

# OpenID

[Configuration Manager](#) [Configuration Manual](#)

☐ Show Password

[Urls](#) [Licence](#) [Database](#) [Active Directory/OpenId](#) [App Logs](#) [Background Jobs](#) [XFrame Settings](#)

[Active Directory](#) **OpenID**

**OpenID Section**

☐ Active ☐ Login using OpenId Groups relations only

**Server Realm**

**Metadata**

**Client ID**

**Client Secret**

**Redirect Uri**

**Infoport Group for Portal Admins**

**LogoutUri**

**Claim that belongs to the username**

**Claim that belongs to the email**

**Claim that belongs to the forename**

**Claim that belongs to the surname**

**Claim that belongs to the groups**

**Scope**

**Scope**

**Scope**

  

- "Active" tells us if we want Infoport to work with OpenID.
- "Login using OpenId Groups relations only" it is possible to set a ban on the login of a user who does not have an OpenID group assigned.

**Server Realm** – fill in the link to the open id server

## Server Realm

**Metadata** – fill in the link to the open id server metadata

## Metadata

**ClientID** – fill in the reference to the Client identifier

Client ID

---

**Client Secret** – insert client secret

Client Secret

---

**Redirect Uri** – enter the url that will be called after logging out of the infoport

Redirect Uri

<https://your-url:443/signin-oidc>

---

**Infoport Group for Portals Admins** – enter the name of the group where you want the Infoport portal administrator users to be

Infoport Group for Portal Admins

/PortalAdmins

---

**LogoutUri** – enter a url that logs out of open id

LogoutUri

[https://openid.test.cz/auth/realms/test/protocol/openid-connect/logout?redirect\\_uri=https://your-url:443](https://openid.test.cz/auth/realms/test/protocol/openid-connect/logout?redirect_uri=https://your-url:443)

---

**Claim that belongs to the username** – specify a claim by which the infoport will pull the infoport username from the response

Claim that belongs to the username

preferred\_username

***Claim that belongs to the email*** – specify a claim by which the infoport will pull the email from the response

Claim that belongs to the email

---

***Claim that belongs to the forename*** – specify a claim by which the infoport will pull the user's first name from the response

Claim that belongs to the forename

---

***Claim that belongs to the surname*** – specify a claim by which the infoport will pull the user's last name from the response

Claim that belongs to the surname

---

***Claim that belongs to the groups*** – specify a claim according to which the infoport will pull the groups to which the user belongs from the response

Claim that belongs to the groups

---

Add ***Open ID Scopes***,to return all necessary attributes

Scope

openid

 DELETE SCOPE

Scope

profile

 DELETE SCOPE

Scope

groups

 DELETE SCOPE

Revision #6

Created 4 May 2022 06:11:57

Updated 23 April 2024 12:33:44 by Karolína Kavanová