

OpenID

The screenshot shows the 'OpenID' configuration page within a 'Configuration Manager' interface. The page has a blue header with 'Configuration Manager' and a link to 'Configuration Manual'. Below the header, there's a navigation bar with tabs: 'Urls', 'Licence', 'Database', 'Active Directory/OpenId', 'App Logs', 'Background Jobs', and 'XFrame Settings'. The 'Active Directory' tab is selected, and the 'OpenID' sub-tab is active. The main content area is titled 'OpenID Section' and contains several configuration fields and sections:

- Active:** A checkbox that is currently unchecked.
- Login using OpenId Groups relations only:** A checkbox that is currently unchecked.
- Server Realm:** A text input field containing 'https://openid.test.cz/auth/realms/test'.
- Metadata:** A text input field containing 'https://openid.test.cz/auth/realms/test/.well-known/openid-configuration'.
- Client ID:** An empty text input field.
- Client Secret:** An empty text input field.
- Redirect Uri:** A text input field containing 'https://your-uri:443/signin-oidc'.
- Infoport Group for Portal Admins:** A text input field containing '/PortalAdmins'.
- LogoutUri:** A text input field containing 'https://openid.test.cz/auth/realms/test/protocol/openid-connect/logout?redirect_uri=https://your-uri:443'.
- Claim that belongs to the username:** A text input field containing 'preferred_username'.
- Claim that belongs to the email:** A text input field containing 'emailaddress'.
- Claim that belongs to the forename:** A text input field containing 'forename'.
- Claim that belongs to the surname:** A text input field containing 'surname'.
- Claim that belongs to the groups:** A text input field containing 'groups'.
- Scope:** A section with three text input fields: 'openid', 'profile', and 'groups'. Each field has a red 'DELETE SCOPE' button next to it.
- Buttons:** A green 'CHECK' button at the bottom left and a blue 'ADD SCOPE' button at the bottom right.

At the bottom of the page, there's a blue footer bar with three buttons: a back button labeled '← ZPĚT', a 'CHECK ALL' button, and a red 'SAVE SETUP & TERMINATE SERVER (AFTER THAT YOU MUST START SERVER AGAIN)' button.

- "Active" tells us if we want Infoport to work with OpenID.
- "Login using OpenId Groups relations only" it is possible to set a ban on the login of a user who does not have an OpenID group assigned.

Server Realm – fill in the link to the open id server

Server Realm

`https://openid.test.cz/auth/realms/test`

Metadata – fill in the link to the open id server metadata

Metadata

`https://openid.test.cz/auth/realms/test/.well-known/openid-config`

ClientID – fill in the reference to the Client identifier

Client ID

Client Secret – insert client secret

Client Secret

Redirect Uri – enter the url that will be called after logging out of the infoport

Redirect Uri

<https://your-url:443/signin-oidc>

Infoport Group for Portals Admins – enter the name of the group where you want the Infoport portal administrator users to be

Infoport Group for Portal Admins

/PortalAdmins

LogoutUri – enter a url that logs out of open id

LogoutUri

https://openid.test.cz/auth/realms/test/protocol/openid-connect/logout?redirect_uri=https://your-url:443

Claim that belongs to the username – specify a claim by which the infoport will pull the infoport username from the response

Claim that belongs to the username

preferred_username

Claim that belongs to the email – specify a claim by which the infoport will pull the email from the response

Claim that belongs to the email

Claim that belongs to the forename – specify a claim by which the infoport will pull the user's first name from the response

Claim that belongs to the forename

Claim that belongs to the surname – specify a claim by which the infoport will pull the user's last name from the response

Claim that belongs to the surname

Claim that belongs to the groups – specify a claim according to which the infoport will pull the groups to which the user belongs from the response

Claim that belongs to the groups

Add ***Open ID Scopes***,to return all necessary attributes

Scope	<input type="text" value="openid"/>	- DELETE SCOPE
Scope	<input type="text" value="profile"/>	- DELETE SCOPE
Scope	<input type="text" value="groups"/>	- DELETE SCOPE

Další související informace s OpenID:

<https://doc.eainfoport.cz/books/uzivatelsky-manual/page/mapovani-skupiny-na-openid>

<https://doc.eainfoport.cz/books/uzivatelsky-manual/page/prihlaseni-uzivatele-ktery-nema-prirazenou-openid-skupinu>

<https://doc.eainfoport.cz/books/otazky-odpovedi/page/chybejici-opravneni-repository-behem-prihlaseni-pres-ad-nebo-openid>

Revision #7

Created 4 May 2022 06:11:57

Updated 19 May 2025 09:15:22 by Karolína Kavanová