

# Scheduler Jobs

Are processes that are activated regularly and serve to keep the application in good condition. These include refreshing data in a memory and disk cache, various data synchronisations, and deleting unnecessary data and system processes.

## Common settings for all scheduled jobs

The basic parameter for each job is information about the frequency with which it will run. It is possible to set it to run every minute, or maybe just once a month.

The syntax known as [CRON](#) is used for this and there are always five items in the configurator (Minute, Hour, Day of the Month, Month and Day of the week).

| Minute                         | Hour                           | Day of the Month               | Month                          | Day of the Week                |
|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| <input type="text" value="0"/> | <input type="text" value="*"/> | <input type="text" value="*"/> | <input type="text" value="*"/> | <input type="text" value="*"/> |

For each job it is also possible to set whether it should be run immediately after the application (server) start by checking the "**Run Immediately**" item.

☐ **Run Immediately**

- [Regenerate Repository Tree Job](#)
- [Regenerate Image](#)
- [CleanDcomJob](#)
- [CleaningDiskCacheJob](#)

---

Revision #11

Created 7 April 2022 11:50:21

Updated 2 November 2023 09:02:57 by Karolína Kavanová