EA Path search

If the user chooses to search by PATH, the element located on the specified path is searched.

In the "*Path to element*" field the user types or pastes the copied ea path (*it is a sequence of packages and elements separated by a dot*) and clicks on the "*Search*" button.


The "*Search*" button redirects the user to the element. The right part shows the artifact detail and the left part shows the artifact marked in the tree.

Repozitář

- EA Infoport Demo
- Example Model
  - Call Behavior
  - ArchiMate
  - Classifiers
  - UML Modeling
  - Domain Specific Modeling
  - Navigate, Search & Trace
  - Enterprise Architecture
  - Analysis and Business Modeling
  - Project Management
  - Testing
  - Maintenance
  - Publishing
  - Reporting
  - Database Modeling
  - Schema Modeling
    - Schema Modeling
      - Schema Composer
        - Class Model
          - Store
            - Store
            - Currency
            - CostType
            - Price
            - Address
            - Amount
            - Store

Store

class Store

Manufacturer
- name: string

+Manufacturer
1
+Manufacturer
0..*

When any named XML or JSON schema facet exists in the Tagged Value domain of an attribute the Schema Composer emits the appropriate restrictions.

Example: The postcode attribute of Address has a length constraint that can be seen in the tagged value list when the attribute is selected.

+Address 1

Address
- city: string
- country: string
- postcode: string
- street: string
- streetno: string

+Address 1..

Store
- jsonexcmin: int
- name: string
- url: string
- xsdexcmin: int

+Store
1
+In

```
<xs:complexType name="Address">
    <xs:sequence>
        <xs:element name="city" minOccurs="1" maxOccurs="1" t
        <xs:element name="country" minOccurs="1" maxOccurs="1
        <xs:element name="postcode" minOccurs="1" maxOccurs="
```

Revision #2
Created 23 May 2022 08:08:43
Updated 31 August 2022 08:56:51